

LS-200/300
Slitter equipment.



Model	LS-200	LS-300
- Weight	2510kg	2910kg
- Dimensions (LxWxH)	4920x3140x1140mm	4920x4040x1140mm
- Pneumatic supply	6 bar	
- Cutting speed	Variable to 20m/min	
- Max. weight of belt slab	1800kg	2400kg
- Max. belt width	2200mm	3200mm
- Min. belt width	100mm	
- Max. belt thickness	10mm	
- Electrical data	400V 3ph 50Hz // 230V 3ph 60Hz	

1. Details equipment

- Motorized unwinder set with opposite disc brake.
- Including “Guttin” folding safety chucks.
- Including 125mm pneumatic shaft + inflating gun.
- Safety barriers for winding area
- Possibility to rewind the belt after slitting steps.
- 4 Division arm + separate storage rack with floor mounting
- Including wired remote controller, for in process correction of belt alignment. Operational from winder/slitter side.
- Upper drum pneumatically pressurized and parallel synchronized.
- 5 knife blocks, with 0.65mm knives .
- Manually adjustable guides with clamping system, able to move over entire width of slitter.
- One guide is split in two parts for guiding steps.
- Mechanical measuring system.
- Safety barriers on top of the guiding area.
- Winder structural frame is included in slitter structural frame